REV.	ECN NO.	DATE	SIGN	DESCRIPTION
01	Initial Release	2021/09/14	Ann	New Item

Part No.:
M16XX−PASH−LS0−F0
- 03: 3Pin
- 04: 4Pin
- B5: 5Pin
- 05: 5Pin
- 06: 6Pin
- B7: 7Pin
- 07: 7Pin
- 08: 8Pin
- 12: 12Pin





5Pin



8Pin



5Pin(05−b)



7Pin



4Pin



7Pin(07−b)



3Pin



6Pin


12Pin

Pin Assignments
Front View

Note:
* IP Grade: IP40
* Rated current: 3Pin~8Pin: 5A
  12Pin: 3A
* Rated voltage: 3Pin~8Pin: 250V
  12Pin: 60V
* Operation Temperature: −20°C~85°C
* Recommend Cable OD: ø6.0mm~8.0mm

PRODACONN

旭達康科技有限公司
Prodaconn
2021/09/14
ISSUSED

NO.	ITEM	SPEC	QTY
12	Gland Nut	Nylon+GF,Black	1
11	Gland Cage	POM,White	1
10	Gland	Silicone,Black	1
9	Back Body	Nylon+GF,Black	1
8	Coat	Copper Alloy,Nickel Plated	1
7	Screw	Spcc,Nickel Plated	1
6	Clamps Body	Zinc Alloy,Nickel Plated	1
5	Clamps	Zinc Alloy,Nickel Plated	1
4	Cap	Zinc Alloy,Nickel Plated	1
3	Insulation	PVC	1
2	Pin	Copper Alloy,Gold Plated	N
1	Housing	Nylon,Black	1

BOM LIST

All dimension in mm

PRODACONN

TOLERANCE UNLESS OTHERWISE SPECIFIED	REV.	SCALE
±0.5	01	1:1

DRAWN BY	APPROVED BY	DATE(Y/M/D)	PAGE	SIZE
Ann	Roy	2021/09/14	1/1	A4

PART NO:	TITLE
M16XX−PASH−LS0−F0	M16 MALE ASSEMBLY
CUSTOMER NO:	

THIS DOCUMENT IS CONFIDENTIAL AND A PROPERTY OF PRODACONN DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY PRODACONN