


Recommend
CABLE ODØ4.5mm ~6.5mm

Note:

- * IP Grade: IP67
- * Rated current: 5A
- * Rated voltage: 250V



All dimension in mm

TOLERANCE UNLESS
OTHERWISE SPECIFIED

±0.5

REV.
01

SCALE
1:1



DRAWN BY
YU-FEI

APPROVED BY
Roy

DATE(Y/M/D)
2021/09/01

PAGE
1/1

SIZE
A4

PART NO:
CBD03-FMAP-LS0-F0


TITLE
Circular Standard Assembly

CUSTOMER NO:

THIS DOCUMENT IS CONFIDENTIAL AND A PROPERTY OF PRODACONN. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY PRODACONN

8	Circular Standard F Conn. M Pin	Sealing Nut: Nylon+GF,Black	1
7		Seal: Rubber	1
6		Clamp Ring: Nylon+GF,Black	1
5		Gasket: Rubber	1
4		Lock Nut: Nylon+GF,Black	1
3		O-Ring: Rubber	1
2		Pin: Copper Alloy,Gold Plated	3
1		Housing: Nylon+GF,Black	1
NO.	ITEM	SPEC	QTY

BOM LIST



Pin Assignments
Front View