


Recommend
CABLE ODØ4.5mm ~6.5mm

Note:

- * IP Grade: IP67
- * Rated current: 5A
- * Rated voltage: 250V

8	Circular Standard F Conn. M Pin	Sealing Nut: Nylon+GF,Black	1
7		Seal: Rubber	1
6		Clamp Ring: Nylon+GF,Black	1
5		Gasket: Rubber	1
4		Lock Nut: Nylon+GF,Black	1
3		O-Ring: Rubber	1
2		Pin: Copper Alloy,Gold Plated	2
1		Housing: Nylon+GF,Black	1
NO.	ITEM	SPEC	QTY

BOM LIST



Pin Assignments
Front View

		All dimension in mm	
		TOLERANCE UNLESS OTHERWISE SPECIFIED ±0.5	REV. 01 SCALE 1:1
DRAWN BY YU-FEI		APPROVED BY Roy	
DATE(Y/M/D) 2021/09/01		PAGE 1/1	SIZE A4
PART NO: CBD02-FMAP-LS0-F0		TITLE Circular Standard Assembly	
CUSTOMER NO:			
THIS DOCUMENT IS CONFIDENTIAL AND A PROPERTY OF PRODACONN. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY PRODACONN			