


Recommend  
CABLE ODØ4.5mm ~6.5mm

Note:

- \* IP Grade: IP67
- \* Rated current: 5A
- \* Rated voltage: 250V

8	Circular Standard F Conn. M Pin	Sealing Nut: Nylon+GF,Black	1
7		Seal: Rubber	1
6		Clamp Ring: Nylon+GF,Black	1
5		Gasket: Rubber	1
4		Lock Nut: Nylon+GF,Black	1
3		O-Ring: Rubber	1
2		Pin: Copper Alloy,Gold Plated	5
1		Housing: Nylon+GF,Black	1
NO.	ITEM	SPEC	QTY

BOM LIST



Pin Assignments  
Front View



All dimension in mm	
TOLERANCE UNLESS OTHERWISE SPECIFIED	REV. 01
±0.5	SCALE 1:1

DRAWN BY	APPROVED BY	DATE(Y/M/D)	PAGE	SIZE
YU-FEI	Roy	2021/09/01	1/1	A4
PART NO:		TITLE		
CBD05-FMAP-LS0-F0		Circular Standard Assembly		
CUSTOMER NO:				
THIS DOCUMENT IS CONFIDENTIAL AND A PROPERTY OF PRODACONN. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY PRODACONN				