


REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2023/02/09	Ann	New Item



Conn.

M5x0.5

PRODACONN

L(mm)

(30.7)

①

②



Part No.:
M5A03-PPNL-MXX

Cable Length

01: 01Meter

02: 02Meters

:

99: 99Meters(Max.)

* Cable Length Tolerance:

1M~5M: ±50mm

5.01M~10M: ±80mm

10.01M~20M: ±100mm

20.01M~30M: ±150mm

30.01M~40M: ±200mm

40.01M~50M: ±250mm

Note:

①* IP Grade: IP67

* Housing: TPU,Black

* Pin: Copper Alloy,Gold Plated

* Nut: Copper Alloy,Satin Nickel Plated


* Shell: Copper Alloy,Bight Tin Plated

②* Cable: UL2517 28AWG*3C,
PVC Jacket,Black

Electrical Characteristics:

* Rated Current: 1A

* Rated Voltage: 60V



Pin Assignments
Front View

4	Black	黑
3	Green	綠
2	White	白
1	Red	紅
Conn.	Wire Color	
Pin Out		

		All dimension in mm	
		TOLERANCE UNLESS OTHERWISE SPECIFIED ±0.5	REV. A
DRAWN BY Ann		APPROVED BY Roy	
PART NO: M5A03-PPNL-MXX		DATE(Y/M/D) 2023/02/09	
CUSTOMER NO:		PAGE 1/1	
TITLE M5 MALE MOLDING TYPE		SIZE A4	
THIS DOCUMENT IS CONFIDENTIAL AND A PROPERTY OF PRODACONN DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY PRODACONN			