REV.	ECN NO.	DATE	SIGN	DESCRIPTION
01	Initial Release	2021/05/05	Ann	New Item







NO.	ITEM	SPEC	QTY
6	Sealing Nut	Nylon,Black	1
5	Clamp Ring	Nylon,Black	1
4	Seal	NBR	1
3	Nut	Zinc Alloy,Nickel Plated	1
2	Pin	Copper Alloy,Gold Plated	4
1	Housing	Nylon,Black	1

BOM LIST



Pin Assignments
Front View

Note:
* IP Grade: IP67
* Rated current: 4A
* Rated voltage: 250V
* Operation Temperature: −25°C~85°C
* Conductor Cross Section: 18AWG Max.
* Cable OD Range: ø4~ø6mm(BK)/ø6~ø8mm(GY)

PRODACONN

All dimension in mm

PRODACONN

TOLERANCE UNLESS OTHERWISE SPECIFIED	REV.
±0.5	01
	SCALE 1:1

DRAWN BY	APPROVED BY	DATE(Y/M/D)	PAGE	SIZE
Ann	Roy	2021/05/05	1/1	A4

PART NO:	TITLE
12A04−PASH−LT0−K0	M12 A−CODE ASSEMBLY
CUSTOMER NO:	

THIS DOCUMENT IS CONFIDENTIAL AND A PROPERTY OF PRODACONN DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY PRODACONN